



Polyester Eye & Eye Flat Web Sling Technical Specs.

- * Polyester Webbing stretch: Approx. 7% at full capacity.
- * Prolonged exposure to UV/ sunlight will degrade Polyester webbing.
- * Polyester webbing starts to degrade at temperatures above 194 degrees Fahrenheit.
- * Fabricated with either Twisted eyes(TE) or Flat eyes(EE).
- * Slings 3" and wider are fabricated with tapered eyes.
- * Available in Scuff Edge material, 1" through 4"

Length Tolerance:

Sling Type Tolerance

1 Ply	+/- 1.5" + 1.5% of length
2 Ply	+/- 2.0" + 2.0% of length
3 Ply	+/- 3.0" + 3.0% of length
4 Ply	+/- 3.0" + 3.0% of length

Flat Web Sling Capacity

	<u>Vertical</u>	<u>Choker</u>	<u>Basket</u>	<u>Min Length</u>
E191 -	1,600	1,250	3,200	3 ft
E192 -	3,200	2,500	6,400	4 ft
E193 -	4,800	3,800	9,600	4 ft
E194 -	6,400	5,000	12,800	4 ft
E196 -	9,600	7,700	19,200	5 ft
E198 -	12,800	10,200	25,600	6 ft
E291 -	3,200	2,500	6,400	3 ft
E292 -	6,400	5,000	12,800	3 ft
E293 -	8,600	6,900	17,200	4 ft
E294 -	11,500	9,200	23,000	4 ft
E296 -	16,300	13,000	32,600	6 ft
E298 -	19,200	15,400	38,400	6 ft
E2910 -	22,400	17,900	44,800	7 ft
E2912 -	26,900	21,500	53,800	8 ft
E391 -	4,100	3,300	8,200	4 ft
E392 -	8,300	6,600	16,600	4 ft
E393 -	12,500	10,000	25,000	5 ft
E394 -	16,000	12,800	32,000	5 ft
E491 -	5,000	4,000	10,000	4 ft
E492 -	10,000	8,000	20,000	4 ft
E493 -	14,900	11,900	29,800	5 ft
E494 -	19,800	15,800	39,600	5 ft



American Made