



# Polyester Round Sling Technical Specs.



- \* Stretch Factor: Approximately 3% at rated capacity.
- \* UV/Sunlight Exposure: Load bearing yarns protected by outer cover.
- \* Polyester round slings start to degrade at temperatures above 194 degrees Fahrenheit.
- \* Length Tolerance of approximately +/-1% of desired length. Matched sets still must be specified at time of order.
- \* Conforms to shape for greater sling life.
- \* Double wall cover for greater sling life.
- \* Every sling individually serialized.



	Vertical	Choker	Basket	Min Length
ENR1 Purple	2,600	2,100	5,200	3 ft.
ENR2 Green	5,300	4,240	10,600	3 ft.
ENR3 Yellow	8,400	6,720	16,800	3 ft.
ENR4 Tan	10,600	8,500	21,200	3 ft.
ENR5 Red	13,200	10,560	26,400	3 ft.
ENR6 Orange	16,800	13,440	33,600	6 ft.
ENR7 Blue	21,200	17,000	42,400	6 ft.
ENR8 Orange	25,000	20,000	50,000	6 ft.
ENR9 Orange	31,000	24,800	62,000	6 ft.
ENR10 Orange	40,000	32,000	80,000	6 ft.
ENR11 Brown	53,000	42,400	106,000	8 ft.
ENR12 Olive	66,000	52,800	132,000	8 ft.
ENR13 Black	90,000	72,000	180,000	8 ft.



American Made